



Double SCHUKO socket outlet with hinged cover surface-mounted Screw terminals, Isopanzer IP44, dark grey/yellow

Technical features

Architecture

Design	according to DIN 49440
Fixing mode	surface-mounting

Configuration

- ample room for wiring under the bases of the inserts

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50 Hz
Rated current	16 A

Electric current

Rated current	16 A
---------------	------

Cover, door

Cover	Complete housing
-------	------------------

Materials

Colour of design line	dark grey/yellow
Design lines special colours	dark grey/yellow
Colour	iron grey
Colour	dark grey
RAL colour	RAL 7011 - Iron grey
Material	thermoplastic
Surface appearance	glossy

Installation, mounting

Installation mode	for horizontal mounting, for screw fastening
- side knock out openings for entries	

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with screw terminals	

Cable

- inserts wired-through
- with one entry for 2 cables and one entry for cable and tube

Use

Differentiation characteristic 3 - Sales	Screw terminals
--	-----------------

4322



IP44

Safety

IK protection code against mechanical impacts	05
Protection index IP	IP44
- without enhanced contact protection	

Identification

Application, usage	Surface-mounted wet-room installation
Main design line	Isopanzer IP44

Instructions

Information text	As a result of the side cable entries specially suited for installation over workbenches.
	Housing screws, hinged cover springs and axles made of stainless steel.