



4280



IP44

**SCHUKO socket outlet with hinged cover surface-mounted Screw terminals, Isopanzer IP44, dark grey/yellow**

**Technical features**

**Architecture**

Design	according to DIN 49440
Fixing mode	surface-mounting

**Configuration**

- ample room for wiring under the bases of the inserts

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50 Hz
Rated current	16 A

**Electric current**

Rated current	16 A
---------------	------

**Cover, door**

Cover	Complete housing
-------	------------------

**Materials**

Colour of design line	dark grey/yellow
Design lines special colours	dark grey/yellow
Colour	iron grey
Colour	dark grey
RAL colour	RAL 7011 - Iron grey
Material	thermoplastic
Surface appearance	glossy

**Installation, mounting**

Installation mode	for screw fastening
-------------------	---------------------

**Connection**

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with screw terminals	

**Cable**

- with cable entry at top and bottom

**Use**

Differentiation characteristic 3 - Sales	Screw terminals
--	-----------------

### Safety

IK protection code against mechanical impacts	05
Protection index IP	IP44
- without enhanced contact protection	

### Identification

Application, usage	Surface-mounted wet-room installation
Main design line	Isopanzer IP44

### Instructions

Information text	Housing screws, hinged cover spring and axle made of stainless steel.
------------------	---