



3045



IP66

**Surface-mounted rotary switch series Isopanzer IP66, dark grey/yellow**

Technical features

**Architecture**

Type of control unit	Short thumb-grip
Fixing mode	surface-mounting

**Configuration**

- series

**Controls and indicators**

- No

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC

**Electric current**

Switching current	16 AX
-------------------	-------

**Materials**

Colour of design line	dark grey/yellow
Design lines special colours	dark grey/yellow
Colour	dark grey
RAL colour	RAL 7011 - Iron grey
Material	thermoplastic
Surface appearance	glossy

**Dimensions**

Depth	61,3 mm
Height	82,2 mm
Width	75 mm

**Installation, mounting**

Installation mode	for screw fastening
-------------------	---------------------

**Connection**

Type of connection	Screw connection
- with screw terminals	

**Cable**

- with cable entry at top and bottom

**Equipment**

- without lighting (cannot be illuminated)

---

**Safety**

---

Protection index IP	IP66
---------------------	------

---

**Identification**

---

Application, usage	Surface-mounted wet-room installation
--------------------	---------------------------------------

---

Main design line	Isopanzer IP66
------------------	----------------

---

**Instructions**

---

Information text	Housing screws made of stainless steel.
------------------	---

---