



471501



SCHUKO socket outlet with hinged cover Splash-protected flush-mounted IP44, brown glossy

Technical features

Architecture

Design	according to DIN 49440
Fixing mode	flush-mounting

Connectivity

Type of USB port	other
------------------	-------

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Rated current	16 A
---------------	------

Cover, door

Cover	Central cover plate
-------	---------------------

Materials

Colour independent of design lines	brown
Colour	brown
Colour	brown
RAL colour	RAL 8011 - Nut brown
Material	thermoplastic
Surface appearance	glossy

Dimensions

Insertion depth	31,2 mm
-----------------	---------

Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

Safety

IK protection code against mechanical impacts	05
Protection index IP	IP44
- without enhanced contact protection	

Identification

Application, usage	Flush-mounted wet-room installation
Main design line	Splash-protected flush-mounted IP44

Instructions

- Only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with the corresponding sealing set.