



471509



**SCHUKO socket outlet with hinged cover Splash-protected flush-mounted IP44, polar white glossy**

Technical features

**Architecture**

Design	according to DIN 49440
Fixing mode	flush-mounting

**Connectivity**

Type of USB port	other
------------------	-------

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

**Electric current**

Rated current	16 A
---------------	------

**Cover, door**

Cover	Central cover plate
-------	---------------------

**Materials**

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	glossy

**Dimensions**

Insertion depth	31,2 mm
-----------------	---------

**Installation, mounting**

Installation mode	with spreader claws
-------------------	---------------------

**Connection**

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

**Safety**

IK protection code against mechanical impacts	05
Protection index IP	IP44
- without enhanced contact protection	

---

**Identification**

---

Application, usage	Flush-mounted wet-room installation
Main design line	Splash-protected flush-mounted IP44

---

**Instructions**

- 
- Only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with the corresponding sealing set.
-