



4246



IP44

Combination rotary switch/SCHUKO socket outlet with hinged cover surface-mounted Change-over switch, Screw terminals, Isopanzer IP44, dark grey/yellow

Technical features

Architecture

Fixing mode	surface-mounting
-------------	------------------

Configuration

- ample room for wiring under the bases of the inserts

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Rated current	16 A

Electric current

Switching current	16 AX
-------------------	-------

Cover, door

Cover	Complete housing
-------	------------------

Materials

Colour of design line	dark grey/yellow
Colour	iron grey
Colour	dark grey
RAL colour	RAL 7011 - Iron grey
Material	thermoplastic
Surface appearance	glossy

Installation, mounting

Installation mode	for vertical mounting, for screw fastening
-------------------	--

Connection

Connection terminals	according to VDE 0620-1:2021-02
- with screw terminals	

Cable

- phase wired-through
- with cable entry at top and bottom

Use

Differentiation characteristic 2 - Sales	Change-over switch
Differentiation characteristic 3 - Sales	Screw terminals

Safety

Protection index IP	IP44
- without enhanced contact protection	

Identification

Application, usage	Surface-mounted wet-room installation
Main design line	Isopanzer IP44

Instructions

Information text	Instead of socket outlets, any other devices from the ISO-reinforced IP44 and IP66 ranges with degree of protection IP44 can be used.
	Housing screws, hinged cover spring and axle made of stainless steel.