



75164090

IP20

B.IQ push-button 4gang KNX - Berker B.IQ, glass polar white

Technical features

Architecture

| | |
|-------------------|----------------|
| Fixing mode | flush-mounting |
| Technical version | 4gang |

Functions

| | |
|---|----|
| With room temperature controller | no |
| - for switch, push-button, dimmer and shutter functions | |

Compatibility

- extension unit for light scene push-button

Controls and indicators

| | |
|---------------------|-----|
| With LED indication | yes |
| Number of buttons | 4 |

Measurement

- dimming / position value transmitter 1 byte

Screen

| | |
|--------------|----|
| With display | no |
|--------------|----|

Materials

| | |
|---------------------------|-----------------------|
| Colour of design line | glass polar white |
| Colour | polarwhite |
| RAL colour | RAL 9010 - Pure white |
| Material | glass |
| Surface appearance | glossy |
| Type of surface treatment | Painted |
| Material family | Glass |

Dimensions

| | |
|-------------------|----------|
| Assembling height | 16,7 mm |
| Height | 118,1 mm |
| Width | 88,5 mm |

LED control

| | |
|-----|---|
| LED | with blue operation LED and 8 white status LEDs |
|-----|---|

Connection

- for bus coupling unit flush-mounted

Scope of delivery

| | |
|-------------------------|----|
| Bus connection included | no |
|-------------------------|----|

Accessories included

| | |
|---|----|
| Inscribable, with labelling field | no |
| <ul style="list-style-type: none">- for installation in single standard wall boxes- for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x- for glass frames in the same "style" for additional applications, see the Design line B.7 | |

Equipment

| | |
|--|--------------------|
| Number of actuation points | 8 |
| With anti-theft/dismantling protection | yes |
| Product type: | product type: B.IQ |

Safety

| | |
|---|------|
| Protection index IP | IP20 |
| Halogen free | no |
| <ul style="list-style-type: none">- with dismantling protection | |

Use conditions

| | |
|-----------------------|------------|
| Operating temperature | -5...45 °C |
|-----------------------|------------|

Identification

| | |
|--------------------------|-----------------------------|
| Application, usage | KNX - operating systems |
| Product family | product family: push-button |
| Main design line | KNX - Berker B.IQ |
| Secondary design line(s) | KNX, Berker B.IQ |