



75161092

IP20

B.IQ push-button 1gang KNX - Berker B.IQ, glass black

Technical features

Architecture

Fixing mode	flush-mounting
Technical version	1gang

Functions

With room temperature controller	no
- for switch, push-button, dimmer and shutter functions	

Compatibility

- extension unit for light scene push-button	
--	--

Controls and indicators

With LED indication	yes
Number of buttons	1

Measurement

- dimming / position value transmitter 1 byte	
---	--

Screen

With display	no
--------------	----

Materials

Colour of design line	glass black
Colour	black
RAL colour	RAL 9005 - Jet black
Material	glass
Surface appearance	glossy
Type of surface treatment	Painted

Dimensions

Assembling height	16,7 mm
Height	88,5 mm
Width	88,5 mm

LED control

LED	with blue operation LED and 2 white status LEDs (labelling field illumination)
-----	--

Connection

- for bus coupling unit flush-mounted	
---------------------------------------	--

Scope of delivery

Bus connection included	no
-------------------------	----

Accessories included

Inscribable, with labelling field	no
<ul style="list-style-type: none">- for installation in single standard wall boxes- for glass frames in the same "style" for additional applications, see the Design line B.7- for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x	

Equipment

Number of actuation points	2
With anti-theft/dismantling protection	yes
Product type:	product type: B.IQ

Safety

Protection index IP	IP20
Halogen free	no
<ul style="list-style-type: none">- with dismantling protection	

Use conditions

Operating temperature	-5...45 °C
-----------------------	------------

Identification

Application, usage	KNX - operating systems
Product family	product family: push-button
Main design line	KNX - Berker B.IQ
Secondary design line(s)	Berker B.IQ, KNX