no



75164092

IP20

Technical features	
Architecture	
Fixing mode	flush-mounting
Technical version	4gang
Functions	
With room temperature controller	n
<ul> <li>for switch, push-button, dimmer and shutter functions</li> </ul>	
Compatibility	
- extension unit for light scene push-button	
Controls and indicators	
With LED indication	yes
Number of buttons	
Measurement	
- dimming / position value transmitter 1 byte	
Screen	
With display	nc
Materials	
Colour of design line	glass black
Colour	black
RAL colour	RAL 9005 - Jet black
Material	glass
Surface appearance	glossy
Type of surface treatment	Paintee
Material family	Glass
Dimensions	
Assembling height	16,7 mm
	118,1 mm
Height	88,5 mm
Height Width	

- for bus coupling unit flush-mounted

## Scope of delivery

Bus connection included

## Accessories included

Inscribable, with labelling field	no
<ul> <li>for installation in single standard wall boxes</li> <li>for glass frames in the same "style" for additional applications, see the Design line B.7</li> <li>for additional products to complement the installation in matching colours/materials, refer to the Desig platform S.1/B.x</li> </ul>	
Equipment	
Number of actuation points	8
With anti-theft/dismantling protection	yes
Product type:	product type: B.IQ
Safety	
Protection index IP	IP20
Halogen free	no
- with dismantling protection	
Use conditions	
Operating temperature	-545 °C
Identification	
Application, usage	KNX - operating systems
Product family	product family: push-button
Main design line	KNX - Berker B.IQ
Secondary design line(s)	KNX, Berker B.IQ