





# B.IQ push-button 4gang for light scenes KNX - Berker B.IQ, polar white matt

Technical features

#### Architecture

Fixing mode flush-mounting

### **Functions**

With room temperature controller

no

- light scene push-buttons can be cascaded
- retrieval, adjustment and storage of 8 light scenes

### **Controls and indicators**

With LED indication	yes
Number of buttons	4

- second operating level for setting load groups via 3-button actuation

#### Measurement

- dimming / position value transmitter 1 byte

#### Screen

With display no

### Materials

Colour of labelling	105,105,105
Colour of design line	polar white
Colour	polarwhite
RAL colour	RAL 9010 - Pure white
Material / workmanship	aluminium, anodised
Material	thermoplastic
Surface appearance	matt
Type of surface treatment	untreated

## **Dimensions**

Height	118,1 mm
Width	88.5 mm

## **LED** control

LED with blue operation LED and 8 white status LEDs (labelling field illumination)

## Connection

Number of load groups (increase on cascading) 8 - for bus coupling unit flush-mounted

# Scope of delivery

Bus connection included no



# **Accessories included**

Inscribable, with labelling field	no
<ul> <li>for installation in single standard wall boxes</li> <li>for additional products to complement the installation in matchin platform S.1/B.x</li> <li>for plastic frames in the same "style" for additional applications,</li> </ul>	
Equipment	
Number of actuation points	8
With anti-theft/dismantling protection	yes
Type of configuration	Laserdruck
Light scenes	max. 8
Product type:	product type: B.IQ
Safety	
Protection index IP	IP20
Halogen free	no
- with dismantling protection	
Use conditions	
Operating temperature	-545 °C
Identification	
Application, usage	KNX - operating systems
Product family	product family: push-button
Main design line	KNX - Berker B.IQ
Secondary design line(s)	KNX, Berker B.IQ