



75168692



## B.IQ push-button 4gang for light scenes KNX - Berker B.IQ, glass black

### Technical features

#### Architecture

Fixing mode	flush-mounting
-------------	----------------

#### Functions

With room temperature controller	no
<ul style="list-style-type: none"> <li>- light scene push-buttons can be cascaded</li> <li>- retrieval, adjustment and storage of 8 light scenes</li> </ul>	

#### Controls and indicators

With LED indication	yes
Number of buttons	4
<ul style="list-style-type: none"> <li>- second operating level for setting load groups via 3-button actuation</li> </ul>	

#### Measurement

<ul style="list-style-type: none"> <li>- dimming / position value transmitter 1 byte</li> </ul>	
---	--

#### Screen

With display	no
--------------	----

#### Materials

Colour of design line	glass black
Colour	black
RAL colour	RAL 9005 - Jet black
Material	glass
Surface appearance	glossy
Type of surface treatment	Painted

#### Dimensions

Assembling height	16,7 mm
Height	118,1 mm
Width	88,5 mm

#### LED control

LED	with blue operation LED and 8 white status LEDs (labelling field illumination)
-----	--

#### Connection

Number of load groups (increase on cascading)	8
<ul style="list-style-type: none"> <li>- for bus coupling unit flush-mounted</li> </ul>	

#### Scope of delivery

Bus connection included	no
-------------------------	----

#### Accessories included

Inscribable, with labelling field	no
<ul style="list-style-type: none"><li>- for installation in single standard wall boxes</li><li>- for glass frames in the same "style" for additional applications, see the Design line B.7</li><li>- for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x</li></ul>	

#### Equipment

Number of actuation points	8
With anti-theft/dismantling protection	yes
Light scenes	max. 8
Product type:	product type: B.IQ

#### Safety

Protection index IP	IP20
Halogen free	no
<ul style="list-style-type: none"><li>- with dismantling protection</li></ul>	

#### Use conditions

Operating temperature	-5...45 °C
-----------------------	------------

#### Identification

Application, usage	KNX - operating systems
Product family	product family: push-button
Main design line	KNX - Berker B.IQ
Secondary design line(s)	KNX, Berker B.IQ