## product sheet 41670069





white glossy

41670069



Architecture	
Fixing mode	flush-mounting
- 2pole + earth	
Main electrical features	
Nominal voltage	125 \
Rated voltage	125 V A
Frequency	50/60 H
Rated current	15.
Cover, door	
Cover	Central cover plat
Materials	
Colour of design line	polar whit
Colour	polarwhit
Colour	white
RAL colour	RAL 9010 - Pure whit
Material	duroplasti
Surface appearance	gloss
Dimensions	
Insertion depth	19 mr
Installation, mounting	
Installation mode	without spreader claws, for screw fastenin
Connection	
Connection terminals	according to IEC 60884-
and the second second to the	
- with screw terminals	
Use	with screw terminal
<b>Use</b> Differentiation characteristic 3 - Sales	with screw terminal
Use Differentiation characteristic 3 - Sales Standards	
Use Differentiation characteristic 3 - Sales Standards Standard	with screw terminal NEMA 5-15
Use Differentiation characteristic 3 - Sales Standards Standard Safety	
Use Differentiation characteristic 3 - Sales Standards Standard Safety IK protection code against mecanical impacts	NEMA 5-15
<ul> <li>with screw terminals</li> <li>Use</li> <li>Differentiation characteristic 3 - Sales</li> <li>Standards</li> <li>Standard</li> <li>Safety</li> <li>IK protection code against mecanical impacts</li> <li>Enhanced contact protection</li> <li>without enhanced contact protection</li> </ul>	NEMA 5-15 0
Use Differentiation characteristic 3 - Sales Standards Standard Safety IK protection code against mecanical impacts Enhanced contact protection - without enhanced contact protection	NEMA 5-15 0
Use Differentiation characteristic 3 - Sales Standards Standard Safety IK protection code against mecanical impacts Enhanced contact protection	NEMA 5-15

Socket outlet with earthing contact USA/CANADA NEMA 5-15 R with screw terminals, Berker Arsys, polar

Berker Arsys



## Instructions

Information text

Not UL-certified.