



6765750001



**Socket outlet with earthing pin with enhanced touch protection, with screw-in lift terminals, Berker Arsys, brown glossy**

Technical features

**Architecture**

|                 |                |
|-----------------|----------------|
| Fixing mode     | flush-mounting |
| - 2pole + earth |                |

**Connectivity**

|                  |       |
|------------------|-------|
| Type of USB port | other |
|------------------|-------|

**Main electrical features**

|                 |          |
|-----------------|----------|
| Nominal voltage | 250 V    |
| Rated voltage   | 250 V AC |
| Frequency       | 50/60 Hz |
| Rated current   | 16 A     |

**Cover, door**

|       |                     |
|-------|---------------------|
| Cover | Central cover plate |
|-------|---------------------|

**Materials**

|                       |                      |
|-----------------------|----------------------|
| Colour of design line | brown                |
| Colour                | brown                |
| Colour                | brown                |
| RAL colour            | RAL 8011 - Nut brown |
| Material              | duroplastic          |
| Surface appearance    | glossy               |

**Dimensions**

|   |         |
|---|---------|
| Insertion depth                         | 32 mm   |
| Installation depth, flush-mounted boxes | 32 mm   |
| Mirror depth                            | 14,7 mm |

**Installation, mounting**

|                   |                     |
|-------------------|---------------------|
| Installation mode | with spreader claws |
|-------------------|---------------------|

**Connection**

|                                |                          |
|--------------------------------|--------------------------|
| Connection terminals           | according to IEC 60884-1 |
| - with screw-in lift terminals |                          |

**Use**

|  |                                |
|--|--------------------------------|
| Differentiation characteristic 2 - Sales | with enhanced touch protection |
| Differentiation characteristic 3 - Sales | with screw-in lift terminals   |

**Safety**

|   |                          |
|---|--------------------------|
| IK protection code against mechanical impacts | 02                       |
| Enhanced contact protection                   | according to IEC 60884-1 |
| - Enhanced contact protection                 |                          |

**Identification**

---

Main design line

Berker Arsys

---