



47272089



## SCHUKO socket outlet 45° Berker R.1/R.3/R.8, polar white glossy

### Technical features

#### Architecture

Design	according to DIN 49440
Fixing mode	flush-mounting

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

#### Electric current

Rated current	16 A
---------------	------

#### Cover, door

Cover	Central cover plate
-------	---------------------

#### Materials

Colour of labelling	105,105,105
Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Material for printing	ASA polar white
Surface appearance	glossy

#### Dimensions

Insertion depth	32 mm
-----------------	-------

#### Installation, mounting

Installation mode	with spreader claws
- for diagonal insertion	

#### Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

#### Settings

Shading parameter	R1_biały
Laser parameter	R1_weiß

#### Equipment

Type of configuration	Laserdruck
-----------------------	------------

---

**Safety**

---

IK protection code against mechanical impacts	05
Protection index IP	IP20
- without enhanced contact protection	

---

**Identification**

---

Main design line	Berker R.1/R.3/R.8
Secondary design line(s)	Berker R.1, Berker R.3, Berker R.8

---

**Instructions**

---

Information text	Specially suited for combining several socket outlets if right angle plugs are used.
------------------	--

---