## product sheet 47432007



47432007

Design	according to DIN 49440
Fixing mode	flush-mounting
Technical version	Imprint "ZSV
Connectivity	
Type of USB port	othe
Main electrical features	
Nominal voltage	250 \
Rated voltage	250 V A0
Frequency	50/60 Hz
Rated current	16 A
Electric current	
Rated current	16 A
Cover, door	
Cover	Central cover plate
Materials	
Design lines special colours	orange
Design lines special colours Colour	
	orange
Colour	orange
Colour Colour	orangi orange RAL 2003 - Pastel orangi
Colour Colour RAL colour	orange orange RAL 2003 - Pastel orange thermoplastic
Colour Colour RAL colour Material	orange orange RAL 2003 - Pastel orange thermoplastic
Colour Colour RAL colour Material Surface appearance	orange orange RAL 2003 - Pastel orange thermoplastic glossy
Colour Colour RAL colour Material Surface appearance <b>Dimensions</b>	orange orange RAL 2003 - Pastel orange thermoplastic gloss 32 mn
Colour Colour RAL colour Material Surface appearance <b>Dimensions</b> Insertion depth	orange orange RAL 2003 - Pastel orange thermoplastic glossy 32 mm
Colour Colour RAL colour Material Surface appearance Dimensions Insertion depth Installation depth, flush-mounted boxes	orange orange RAL 2003 - Pastel orange thermoplastic glossy 32 mm 31 mm
Colour Colour Colour RAL colour Material Surface appearance Dimensions Insertion depth Installation depth, flush-mounted boxes Installation, mounting	orange orange RAL 2003 - Pastel orange thermoplastic glossy 32 mm 31 mm
Colour Colour Colour RAL colour Material Surface appearance Dimensions Insertion depth Installation depth, flush-mounted boxes Installation, mounting Installation mode	orange orange orange RAL 2003 - Pastel orange thermoplastic glossy 32 mm 31 mm 31 mm with spreader claws according to IEC 60884-1

SCHUKO socket outlet "ZSV" imprint Berker R.1/R.3/R.8, orange glossy

Technical features

## Safety

IK protection code against mecanical impacts	05
Protection index IP	IP20
- without enhanced contact protection	



## Identification

Main design line	Berker R.1/R.3/R.8
Secondary design line(s)	Berker R.1, Berker R.3, Berker R.8

## Instructions

Information text

Insert colour-coded.