



6765762089



Socket outlet with earthing pin with enhanced touch protection, with screw-in lift terminals, Berker R.1/R.3/R.8, polar white glossy

Technical features

Architecture

Fixing mode	flush-mounting
- 2pole + earth	

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Cover, door

Cover	Central cover plate
-------	---------------------

Materials

Colour of labelling	105,105,105
Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Material for printing	ASA polar white
Surface appearance	glossy

Dimensions

Insertion depth	32 mm
-----------------	-------

Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

Connection

Connection terminals	according to IEC 60884-1
- with screw-in lift terminals	

Settings

Shading parameter	R1_bialy
Laser parameter	R1_weiß

Equipment

Type of configuration	Laserdruck
-----------------------	------------

Use

Differentiation characteristic 2 - Sales	with enhanced touch protection
Differentiation characteristic 3 - Sales	with screw-in lift terminals

Safety

IK protection code against mechanical impacts	05
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- Enhanced contact protection	

Identification

Main design line	Berker R.1/R.3/R.8
Secondary design line(s)	Berker R.1, Berker R.3, Berker R.8
