


20309004



**Temperature controller, NC contact, with centre plate with rocker switch, Berker Arsys, stainless steel matt, lacquered**

Technical features

**Functions**

- with on/off switch and indicator LED for "on"

**Main electrical features**

|                 |          |
|-----------------|----------|
| Nominal voltage | 250 V    |
| Rated voltage   | 250 V AC |
| Frequency       | 50/60 Hz |

**Electric current**

|   |          |
|---|----------|
| Inductive load at $\cos \varphi = 0.6$              | max. 4 A |
| Switching current "Heating" at $\cos \varphi = 0.6$ | 4 A      |
| Heating switching current                           | 10 A     |
| Switching current                                   | 10 A     |

**Measurement**

|                       |           |
|-----------------------|-----------|
| Range of temperatures | 5 / 30 °C |
|-----------------------|-----------|

**Materials**

|                        |                 |
|------------------------|-----------------|
| Colour of design line  | stainless steel |
| Colour                 | stainless steel |
| Material / workmanship | lacquered       |
| Material               | Plastic/metal   |

**Installation, mounting**

|                   |                        |
|-------------------|------------------------|
| Installation mode | without spreader claws |
|-------------------|------------------------|

**Connection**

|                          |   |
|--------------------------|---|
| Connection               | with separate connection for night lowering |
| - with plug-in terminals |   |

**Equipment**

|  |         |
|--|---------|
| Night lowering                                       | ≈ 4 K   |
| Switching temperature difference                     | ≈ 0,5 K |
| - setting knob with temperature range limitation     |         |
| - e.g. for valve drives closed in de-energised state |         |

**Use**

|  |                    |
|--|--------------------|
| Differentiation characteristic 1 - Sales | with rocker switch |
|--|--------------------|

**Use conditions**

|                         |        |
|-------------------------|--------|
| Energy efficiency class | I (1%) |
| - with thermal return   |        |

**temperatur**

---

|             |           |
|-------------|-----------|
| Temperature | 5...30 °C |
|-------------|-----------|

---

**Identification**

---

|                    |              |
|--------------------|--------------|
| Application, usage | HVAC control |
| Main design line   | Berker Arsys |

---