


20310002



**Temperature controller, NC contact, with centre plate, 24 V AC/DC with rocker switch, Berker Arslys, white glossy**

Technical features

**Functions**

- with on/off switch and indicator LED for "on"

**Main electrical features**

Nominal voltage	24 V
Rated voltage	24 V AC/DC
Frequency	50/60 Hz

**Electric current**

Switching current	10 A~/4 A=
Switching current "Heating" at $\cos \varphi = 0.6$	4 A
Heating switching current	10 A

**Measurement**

Range of temperatures	5 / 30 °C
-----------------------	-----------

**Materials**

Colour of design line	white
Colour	white
Material	Plastic/metal

**Installation, mounting**

Installation mode	without spreader claws
-------------------	------------------------

**Connection**

Connection	with separate connection for night lowering
- with plug-in terminals	

**Equipment**

Night lowering	≈ 4 K
Switching temperature difference	≈ 0,5 K
- setting knob with temperature range limitation	
- e.g. for valve drives closed in de-energised state	

**Use**

Differentiation characteristic 1 - Sales	with rocker switch
--	--------------------

**Use conditions**

Energy efficiency class	I (1%)
- with thermal return	

**temperatur**

Temperature	5...30 °C
-------------	-----------

**Identification**

---

Application, usage	HVAC control
Main design line	Berker Arsys

---