




474521



SCHUKO socket outlet Mounting orientation variable in 45° steps, Serie 1930/Glas, black glossy

Technical features

Architecture

| | |
|-------------|------------------------|
| Design | according to DIN 49440 |
| Fixing mode | flush-mounting |

Connectivity

| | |
|------------------|-------|
| Type of USB port | other |
|------------------|-------|

Main electrical features

| | |
|-----------------|----------|
| Nominal voltage | 250 V |
| Rated voltage | 250 V AC |
| Frequency | 50/60 Hz |
| Rated current | 16 A |

Electric current

| | |
|---------------|------|
| Rated current | 16 A |
|---------------|------|

Cover, door

| | |
|-------|---------------------|
| Cover | Central cover plate |
|-------|---------------------|

Materials

| | |
|-----------------------|----------------------|
| Colour of design line | black |
| Colour | black |
| Colour | deep black |
| RAL colour | RAL 9005 - Jet black |
| Material | duroplastic |
| Surface appearance | glossy |

Dimensions

| | |
|---|-------|
| Insertion depth | 32 mm |
| Installation depth, flush-mounted boxes | 31 mm |

Installation, mounting

| | |
|-------------------|---------------------|
| Installation mode | with spreader claws |
|-------------------|---------------------|

Connection

| | |
|--------------------------|---------------------------------|
| Connection terminals | according to IEC 60884-1 |
| Connection terminals | according to VDE 0620-1:2021-02 |
| - with plug-in terminals | |

Use

| | |
|--|--|
| Differentiation characteristic 3 - Sales | Mounting orientation variable in 45° steps |
|--|--|

Safety

| | |
|---|------|
| IK protection code against mechanical impacts | 02 |
| Protection index IP | IP20 |

- without enhanced contact protection

Identification

| | |
|--------------------------|---|
| Main design line | Serie 1930/Glas |
| Secondary design line(s) | Serie 1930, Serie 1930 Porzellan Made by Rosenthal, Serie Glass |
