




67687901



**Socket outlet with earthing pin Installation position variable in 45° steps, with enhanced touch protection, Serie 1930/Glas, black glossy**

#### Technical features

#### Architecture

Fixing mode	flush-mounting
- 2pole + earth	

#### Connectivity

Type of USB port	other
------------------	-------

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Rated current	16 A

#### Cover, door

Cover	Central cover plate
-------	---------------------

#### Materials

Colour of design line	black
Colour	black
Colour	deep black
RAL colour	RAL 9005 - Jet black
Material	duroplastic
Surface appearance	glossy

#### Dimensions

Insertion depth	31,3 mm
Installation depth, flush-mounted boxes	31 mm
Mirror depth	14,5 mm

#### Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

#### Connection

Connection terminals	according to IEC 60884-1
- with plug-in terminals	

#### Use

Differentiation characteristic 1 - Sales	Installation position variable in 45° steps
Differentiation characteristic 2 - Sales	with enhanced touch protection

#### Safety

IK protection code against mechanical impacts	02
Enhanced contact protection	according to IEC 60884-1
- Enhanced contact protection	

**Identification**

---

Main design line	Serie 1930/Glas
Secondary design line(s)	Serie 1930, Serie 1930 Porzellan Made by Rosenthal, Serie Glass, Series R.classic

---