

85141131

IP20

**Button 1gang Berker R.1/R.3/R.8/Serie 1930/R.classic, black glossy**

Technical features

**Controls and indicators**

- with 2-push-buttons operation concept

**Main electrical features**

| | |
|---|---|
| Nominal voltage | 12 V |

**Voltage**

| | |
|---|---|
| Operating voltage | via insert |

**Measurement**

| | |
|---|---|
| Relative humidity (without condensation) | 0…65 % (without condensation) |

**Materials**

| | |
|---|---|
| Colour of labelling | 217,217,217 |
| Colour of design line | black |
| Colour | black |
| Material | thermoplastic |
| Material for printing | PC-PMA black |

**Dimensions**

| | |
|---|---|
| Diameter | 57,4 mm |

**Settings**

| | |
|---|---|
| Shading parameter | R1_czarny |
| Laser parameter | R1_schwarz |

**Equipment**

| | |
|---|---|
| Type of configuration | Laserdruck |

- switch-on brightness level for use on dimmer insert, power failure proof, storable

**Use conditions**

| | |
|---|---|
| Operating temperature | -5…45 °C |

- low intrinsic energy requirement

**Identification**

| | |
|---|---|
| Application, usage | Light control |
| Main design line | Berker R.1/R.3/R.8/Serie 1930/R.classic |
| Secondary design line(s) | Electronics platform, Berker R.1, Berker R.3, Berker R.8 |

**Instructions**

- Note:
  When integrating this product into the Serie 1930, the 1gang frame for centre plate Ø 58 mm, order no.: 1382 0... may only be used. Installation in multiple combinations of the Serie 1930 is not possible!