



3315402089



VGA socket outlet Berker R.1/R.3/R.8, polar white glossy

Technical features

Connectivity

- with straight outlet
- S-VGA compatible
- with 15pole D-subminiature jack (front)

Frequency

Frequency range video max. 160 MHz

Screen

Resolution max. 1280 x 1024 px

Materials

Colour of labelling	105,105,105
Colour of design line	polar white
Colour	polarwhite
RAL colour	RAL 9010 - Pure white
Material	Plastic/metal
Material for printing	ASA polar white
Surface appearance	glossy

Dimensions

Insertion depth 12 mm

Installation, mounting

Installation mode without spreader claws, for screw fastening

Connection

Connection with 15pole D-subminiature double jack
 - with backside jack for connecting to pre-assembled VGA cable

Settings

Shading parameter R1_biały
 Laser parameter R1_weiß

Equipment

Type of configuration Laserdruck
 - with supporting ring

Identification

Application, usage Communication technology
 Main design line Berker R.1/R.3/R.8
 Secondary design line(s) Berker R.1, Berker R.3, Berker R.8

Instructions

Information text

For connecting PCs, notebooks, etc. to display devices such as monitors (including LCD monitors) and projectors., Observe the instructions of the cable and device manufacturers for maximum VGA cable lengths!, Fränkische: "Multimedia tube" for laying pre-assembled connection cable, Art. no. 294.10.092, Installation recommendation: Kaiser: "Electronic box" for compliance with the permissible bending radii, Art. No. 1068-02 or 9062-74
