



85342131





# Motion detector 2.2 m Berker R.1/R.3/R.8/Serie 1930/R.classic, black glossy

Technical features

### Architecture

Fixing mode flush-mounting

### **Functions**

- $\mu$ -processor controlled mode of operation
- Teach function for response brightness via button
- with keylock
- Party function for switching on for 2 hours
- with memory function for presence simulation

# **Controls and indicators**

- with button for on/off/automatic

### Measurement

Relative humidity (without condensation)	065 % (without condensation)
Detection field, rectangular shaped	≈ 8 x 12 m

### Reach distance

Range, frontal	≈ 8 m
Range, side	each ≈ 6 m

### Detection

Number of detection levels	3
Detection angle, settable	each side ≈ 4590 °

#### Materials

Colour of design line	black
Colour	black
Material	thermoplastic

# **Dimensions**

Assembling height	34 mm
Nominal mounting height	2,2 m
Diameter	57,6 mm

# **Lighting control**

# **LED** control

LED	with operation and status LED, red/green/orange,
	LED application module/insert compatibility display



# Settings

yes
yes
10100 %
≈ 180 s
30 s

# Safety

Protection index IP	IP20
- with dismantling protection	

# Use conditions

Operating temperature	-545 °C
- low intrinsic energy requirement	

# Identification

Application, usage	Motion detector
Main design line	Berker R.1/R.3/R.8/Serie 1930/R.classic
Secondary design line(s)	Motion detector, Berker R.1, Berker R.3, Berker R.8

### Instructions

- Note:

When integrating this product into the Serie 1930, the 1gang frame for centre plate Ø 58 mm, order no.: 1382 0... may only be used. Installation in multiple combinations of the Serie 1930 is not possible!