



47063522



**SCHUKO socket outlet insert with hinged cover surface-mounted/flush-mounted Berker W.1, polar white matt**

Technical features

**Architecture**

Design	according to DIN 49440
Fixing mode	flush-mounting or surface-mounting

**Connectivity**

Type of USB port	other
------------------	-------

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

**Electric current**

Rated current	16 A
---------------	------

**Cover, door**

Cover	Complete housing
- with hinged cover that falls back, manual clip-in	

**Materials**

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	matt

**Installation, mounting**

Installation mode	for screw fastening
-------------------	---------------------

**Connection**

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with plug-in terminals	

**Safety**

IK protection code against mechanical impacts	05
Protection index IP	IP55
- without enhanced contact protection	

**Use conditions**

Operating temperature	-40...30 °C
Storage/transport temperature	-50...50 °C

---

**Identification**

---

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

---

**Instructions**

---

Information text	Pins of quick-release lock made of ZAMAK
------------------	--

---

- Inserts will only reach the degree of protection IP55 if mounted with a housing surface mounted or frame for flush-mounted installation.

---