



47063525



SCHUKO socket outlet insert with hinged cover surface-mounted/flush-mounted Berker W.1, grey matt

Technical features

Architecture

Design	according to DIN 49440
Fixing mode	flush-mounting or surface-mounting

Connectivity

Type of USB port	other
------------------	-------

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Rated current	16 A
---------------	------

Cover, door

Cover	Complete housing
-	with hinged cover that falls back, manual clip-in

Materials

Colour of design line	grey
Colour	light grey
Colour	dark grey
RAL colour	RAL 7011 - Iron grey
Material	thermoplastic
Surface appearance	matt

Installation, mounting

Installation mode	for screw fastening
-------------------	---------------------

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
-	with plug-in terminals

Safety

IK protection code against mechanical impacts	05
Protection index IP	IP55
-	without enhanced contact protection

Use conditions

Operating temperature	-40...30 °C
Storage/transport temperature	-50...50 °C

Identification

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

Instructions

Information text	Pins of quick-release lock made of ZAMAK
<ul style="list-style-type: none">- Inserts will only reach the degree of protection IP55 if mounted with a housing surface mounted or frame for flush-mounted installation.	