



47703522



IP55

## SCHUKO socket outlet 2gang vertical with hinged cover surface-mounted Berker W.1, polar white matt

### Technical features

#### Architecture

Design	according to DIN 49440
Fixing mode	surface-mounting

#### Configuration

- ample room for wiring under the bases of the inserts

#### Connectivity

Type of USB port	other
------------------	-------

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

#### Electric current

Rated current	16 A
---------------	------

#### Cover, door

Cover	Complete housing
- with hinged cover that falls back, manual clip-in	

#### Materials

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	matt

#### Installation, mounting

Installation mode	for vertical mounting, for screw fastening
-------------------	--------------------------------------------

#### Connection

Conductor cross-section	1...2,5 mm <sup>2</sup>
Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
- with two clip-in places for Wago 2-wire connection terminals in the housing floor	
- with Wago clip-in 2-wire connection terminal for wiring	
- with plug-in terminals	

#### Cable

- inserts wired-through
- with one entry for 2 cables and one entry for cable and tube

---

**Equipment**

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

---

**Safety**

IK protection code against mechanical impacts 05

Protection index IP IP55

---

- without enhanced contact protection

---

**Use conditions**

Operating temperature -40...30 °C

Storage/transport temperature -50...50 °C

---

**Identification**

Application, usage Surface-mounted wet-room installation

Main design line Berker W.1

---

**Instructions**

Information text Hinged cover springs made of stainless steel, pins  
of quick-release lock made of ZAMAK

---