



47803525



IP55

Combination change-over switch/SCHUKO socket outlet with hinged cover surface-mounted with enhanced touch protection, Berker W.1

Technical features

Architecture

Fixing mode	surface-mounting
-------------	------------------

Configuration

- ample room for wiring under the bases of the inserts

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Switching current	10 AX
-------------------	-------

Cover, door

- with hinged cover that falls back, manual clip-in

Materials

Colour	iron grey
Colour	dark grey
RAL colour	RAL 7011 - Iron grey
Material	thermoplastic
Surface appearance	mat

Installation, mounting

Installation mode	for vertical mounting
-------------------	-----------------------

Connection

- with plug-in terminals

Cable

- with one entry for 2 cables and one entry for cable and tube

Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside
- change-over switch and socket outlet connectable separately

Use

Differentiation characteristic 2 - Sales	with enhanced touch protection
--	--------------------------------

Safety

Protection index IP	IP55
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02

Use conditions

Operating temperature	-40...30 °C
Storage/transport temperature	-50...50 °C

Identification

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

Instructions

Information text	Hinged cover springs made of stainless steel, pins of quick-release lock made of ZAMAK
------------------	--