



47903522



IP55

Combination series switch/SCHUKO socket outlet with hinged cover surface-mounted with enhanced touch protection, Berker W.1, polar white matt

Technical features

Architecture

Fixing mode surface-mounting

Configuration

- ample room for wiring under the bases of the inserts

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Switching current 10 AX

Cover, door

Cover Complete housing

- with hinged cover that falls back, manual clip-in

Materials

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	matt

Installation, mounting

Installation mode for vertical mounting

Connection

Connection terminals according to VDE 0620-1:2021-02

- with Wago clip-in 2-wire connection terminal for wiring
- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- with plug-in terminals

Cable

- with one entry for 2 cables and one entry for cable and tube

Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside
- series switch and socket outlet connectable separately

Use

Differentiation characteristic 2 - Sales with enhanced touch protection

Safety

Protection index IP	IP55
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- Enhanced contact protection	

Use conditions

Operating temperature	-40...30 °C
-----------------------	-------------

Identification

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

Instructions

Information text	Hinged cover springs made of stainless steel, pins of quick-release lock made of ZAMAK
------------------	--
