



10112245



Frame 1gang Berker R.3, black glossy

Technical features

Architecture

| | |
|-------------------|-------|
| Technical version | 1gang |
|-------------------|-------|

Capacity

| | |
|-------------------|---|
| Number of sockets | 1 |
|-------------------|---|

Materials

| | |
|---------------------|-------------|
| Colour of labelling | 217,217,217 |
|---------------------|-------------|

| | |
|-----------------------|-------|
| Colour of design line | black |
|-----------------------|-------|

| | |
|--------|-------|
| Colour | black |
|--------|-------|

| | |
|--------|------------|
| Colour | deep black |
|--------|------------|

| | |
|------------|----------------------|
| RAL colour | RAL 9005 - Jet black |
|------------|----------------------|

| | |
|----------|---------------|
| Material | thermoplastic |
|----------|---------------|

| | |
|-----------------------|--------------|
| Material for printing | PC-PMA black |
|-----------------------|--------------|

| | |
|--------------------|--------|
| Surface appearance | glossy |
|--------------------|--------|

| | |
|---------------------------|-----------|
| Type of surface treatment | untreated |
|---------------------------|-----------|

Dimensions

| | |
|-------|--------|
| Depth | 9,9 mm |
|-------|--------|

| | |
|--------|---------|
| Height | 80,7 mm |
|--------|---------|

| | |
|-------|---------|
| Width | 80,7 mm |
|-------|---------|

Installation, mounting

| | |
|-------------------|---|
| Installation mode | for vertical and horizontal mounting, clamp fastening |
|-------------------|---|

Settings

| | |
|-------------------|-----------|
| Shading parameter | R1_czarny |
|-------------------|-----------|

| | |
|-----------------|------------|
| Laser parameter | R1_schwarz |
|-----------------|------------|

Equipment

| | |
|-----------------------|------------|
| Type of configuration | Laserdruck |
|-----------------------|------------|

Safety

| | |
|---------------------|------|
| Protection index IP | IP20 |
|---------------------|------|

Identification

| | |
|------------------|------------|
| Main design line | Berker R.3 |
|------------------|------------|

Instructions

- Only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with the corresponding sealing set.