

75161594

IP20

B.IQ push-button 1gang comfort KNX - Berker B.IQ, Aluminium, aluminium anodised

Technical features

	cture

Fixing mode	flush-mounting
Technical version	1gang

Functions

With room temperature controller	no
- for switch, push-button, dimmer and shutter functions	

Compatibility

- extension unit for light scene push-button

Controls and indicators

With LED indication	yes
Number of buttons	1

- activation of second user level via object
- one push-button operation for switching, pushing, shutters and dimming

Measurement

- value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

Screen

With display no

Materials

Aluminium
aluminium
RAL 9006 - White aluminium
aluminium, anodised
Aluminium
matt
Anodised

Dimensions

Assembling height	16,7 mm
Height	88,5 mm
Width	88,5 mm

LED control

LED	with blue operation LED and 2 white status LEDs
	(labelling field illumination)

Connection

- for bus coupling unit flush-mounted



Settings	
Supported configuration modes	system, PB
- single and two push-button operation parameterisable	
Scope of delivery	
Bus connection included	no
Accessories included	
Inscribable, with labelling field	no
 for installation in single standard wall boxes for aluminium frames in the same "style" for additional applications, see for additional products to complement the installation in matching colo platform S.1/B.x 	
Equipment	
Number of actuation points	2
With anti-theft/dismantling protection	yes
Product type:	product type: B.IQ
Safety	
Protection index IP	IP20
Halogen free	no
 with dismantling protection alarm telegram after disconnection from bus coupling unit 1 bit or 1 byt 	re
Use conditions	
Operating temperature	-545 °C
Identification	
Application, usage	KNX - operating systems
Product family	product family: push-button
Main design line	KNX - Berker B.IQ
Secondary design line(s)	KNX, Berker B.IQ