



75163594

**IP20** 

## B.IQ push-button 3gang comfort KNX - Berker B.IQ, Aluminium, aluminium anodised

Technical features

-		• -		_	
Λ	rol	١ıt	ect		rο

Fixing mode	flush-mounting
Technical version	3gang

#### **Functions**

W	ith room temperature controller	no
-	for switch, push-button, dimmer and shutter functions	

## Compatibility

- extension unit for light scene push-button

## **Controls and indicators**

With LED indication	yes
Number of buttons	3

- activation of second user level via object
- one push-button operation for switching, pushing, shutters and dimming

# Measurement

- value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

#### Screen

With display no

### Materials

Colour of design line	Aluminium
Colour	aluminium
RAL colour	RAL 9006 - White aluminium
Material / workmanship	aluminium, anodised
Material	Aluminium
Surface appearance	matt
Type of surface treatment	Anodised

#### **Dimensions**

Assembling height	16,7 mm
Height	88,5 mm
Width	88,5 mm

## LED control

LED	with blue operation LED and 6 white status LEDs
	(labelling field illumination)

## Connection

- for bus coupling unit flush-mounted



Settin	ıgs

ock.ingo	
Supported configuration modes	system, PB
- single and two push-button operation parameterisable	
Scope of delivery	
Bus connection included	no
Accessories included	
Inscribable, with labelling field	no
<ul> <li>for installation in single standard wall boxes</li> <li>for additional products to complement the installation in match platform S.1/B.x</li> <li>for aluminium frames in the same "style" for additional applical</li> </ul>	
- Tot auditimidit traines in the same style for additional application	ions, see the besign line b.7
Equipment	
Number of actuation points	6
With anti-theft/dismantling protection	yes
Product type:	product type: B.IQ
Safety	
Protection index IP	IP20
Halogen free	no
<ul> <li>with dismantling protection</li> <li>alarm telegram after disconnection from bus coupling unit 1 bit</li> </ul>	t or 1 byte
Use conditions	
Operating temperature	-545 °C
Identification	
Application, usage	KNX - operating systems
Product family	product family: push-button
Main design line	KNX - Berker B.IQ
Secondary design line(s)	KNX, Berker B.IQ