no



75164594

IP20

B.IQ push-button 4gang comfort KNX - Berker B.IQ, Aluminium, aluminium anodised

Technical features

Architecture

Fixing mode	flush-mounting
Technical version	4gang

Functions

With room temperature controller	no
- for switch, push-button, dimmer and shutter functions	

Compatibility

- extension unit for light scene push-button

Controls and indicators

With LED indication	yes
Number of buttons	4

- second operating level via object or 3-button handle
- lockable via 3-button actuation
- one push-button operation for switching, pushing, shutters and dimming

Measurement

- value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

Screen

With display

Materials

Colour of design line	Aluminium
Colour	aluminium
RAL colour	RAL 9006 - White aluminium
Material / workmanship	aluminium, anodised
Material	Aluminium
Surface appearance	matt
Type of surface treatment	Anodised

Dimensions

Assembling height	16,7 mm
Height	118,1 mm
Width	88,5 mm

LED control

LED	with blue operation LED and 8 white status LEDs
	(labelling field illumination)

Connection

- for bus coupling unit flush-mounted



Settings

Supported configuration modes	system, PE
- single and two push-button operation parameterisable	
Scope of delivery	
Bus connection included	no
Accessories included	
Inscribable, with labelling field	n
 for installation in single standard wall boxes for additional products to complement the installation in match platform S.1/B.x for aluminium frames in the same "style" for additional applica 	
Equipment	
Number of actuation points	8
With anti-theft/dismantling protection	yes
Product type:	product type: B.IC
Safety	
Protection index IP	IP20
Halogen free	na
 with dismantling protection alarm telegram after disconnection from bus coupling unit 1 bit 	it or 1 byte
Use conditions	
Operating temperature	-545 °(
Identification	
Identification Application, usage	KNX - operating systems
	KNX - operating systems product family: push-buttor
Application, usage	