



75162593

IP20

**B.IQ push-button 2gang comfort KNX - Berker B.IQ, Stainless steel, metal brushed**

Technical features

**Architecture**

Fixing mode	flush-mounting
Technical version	2gang

**Functions**

With room temperature controller	no
- for switch, push-button, dimmer and shutter functions	

**Compatibility**

- extension unit for light scene push-button

**Controls and indicators**

With LED indication	yes
Number of buttons	2
- activation of second user level via object	
- one push-button operation for switching, pushing, shutters and dimming	

**Measurement**

- value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

**Screen**

With display	no
--------------	----

**Materials**

Colour of design line	Stainless steel
Colour	stainless steel
RAL colour	RAL 9022 - Pearl light grey
Material / workmanship	metal brushed
Material	stainless steel
Surface appearance	matt
Type of surface treatment	brushed

**Dimensions**

Assembling height	16,7 mm
Height	88,5 mm
Width	88,5 mm

**LED control**

LED	with blue operation LED and 4 white status LEDs (labelling field illumination)
-----	--

**Connection**

- for bus coupling unit flush-mounted

### Settings

Supported configuration modes	system, PB
- single and two push-button operation parameterisable	

### Scope of delivery

Bus connection included	no
-------------------------	----

### Accessories included

Inscribable, with labelling field	no
- for installation in single standard wall boxes	
- for stainless steel frames in the same "style" for additional applications, see the Design line B.7	
- for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x	

### Equipment

Number of actuation points	4
With anti-theft/dismantling protection	yes
Product type:	product type: B.IQ

### Safety

Protection index IP	IP20
Halogen free	no
- with dismantling protection	
- alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte	

### Use conditions

Operating temperature	-5...45 °C
-----------------------	------------

### Identification

Application, usage	KNX - operating systems
Product family	product family: push-button
Main design line	KNX - Berker B.IQ
Secondary design line(s)	KNX, Berker B.IQ