



SCHUKO socket outlet 2gang horizontal with hinged cover surface-mounted with labelling field, Locks - differing lockings, enhanced contact protection, Berker W.1, polar white matt

Technical features

Architecture

Fixing mode	surface-mounting
Technical version	4 cable entries

Configuration

- ample room for wiring under the bases of the inserts

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50 Hz
Rated current	16 A

Electric current

Rated current	16 A
---------------	------

Cover, door

Cover	Complete housing
- with hinged cover that falls back, manual clip-in	

Materials

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	matt

Dimensions

Labelling field (W x H)	50 x 16 mm
Height	76 mm
Width	147 mm

Installation, mounting

Installation mode	for horizontal mounting, for screw fastening
-------------------	--

Connection

Connection terminals	according to IEC 60884-1
- with two clip-in places for Wago 2-wire connection terminals in the housing floor - with Wago clip-in 2-wire connection terminal for wiring - with plug-in terminals	

Cable

- 2 additional side cable entries
- with one entry for 2 cables and one entry for cable and tube

47893522



IP55

Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

Use

Differentiation characteristic 1 - Sales	with labelling field
Differentiation characteristic 2 - Sales	Locks - differing lockings
Differentiation characteristic 3 - Sales	enhanced contact protection

Safety

IK protection code against mechanical impacts	05
Protection index IP	IP55
- Enhanced contact protection - with 4 identical keys	

Use conditions

Operating temperature	-40...30 °C
Storage/transport temperature	-50...50 °C

Identification

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

Instructions

Information text	Hinged cover springs made of stainless steel, pins of quick-release lock made of ZAMAK, Spare keys and other closures (max. 24) on request., As a result of the side cable entries specially suited for installation over workbenches., Housing screws, hinged cover springs made of stainless steel., Labelling field height arranged for P-touch strips 12 mm.
- The upper and lower entry for cables are laterally offset and therefore particularly suitable for mounting beside door frame or the like - The locks of an article do have identical lockings. When ordering several articles those do usually have differing lockings.	