


283410



## Universal rotary dimmer with centre plate (R, L, C) Soft-lock, polar white glossy

### Technical features

### Functions

- bulb-preserving soft startup

### Main electrical features

Nominal voltage 230 V

### Voltage

Operating voltage 230 V AC

- voltage test possible without dismantling

### Fuse

Fuse short-circuit and overload proof (electronic fuse)

### Power

Dimmable conventional transformers 50...420 VA

connected load 50...420 W/VA

Loss power at full load ≈ 5 W

Electronic transformers 50...420 W

### Measurement

Extension unit input with input for extension units insert for universal rotary dimmer

### Materials

Colour of design line polar white

Colour polarwhite

Material Plastic/metal

### Dimensions

Axis dimension Ø 4 mm

### Incandescent bulbs control

230 V incandescent lamps and halogen lamps 50...420 W

### Installation, mounting

Installation mode for screw fastening

### Connection

Type of load universal

- with plug-in terminals

### Scope of delivery

- with incremental encoder

---

**Equipment**

- phase cut-on or cut-off according to load type, self-learning
  - very low noise
  - with brightness memory
- 

**Use**

---

Differentiation characteristic 3 - Sales	Soft-lock
--	-----------

---

**Use conditions**

---

Operating temperature	5...25 °C
-----------------------	-----------

---

**Identification**

---

Release issue	2
Secondary design line(s)	Serie 1930, Serie 1930 Porzellan Made by Rosenthal, Serie Glass, Series R.classic

---

**Instructions**

---

Information text	Trouble-free operation will be obtained only with Berker TronicÂ® transformers.
------------------	---

---