



75665592



B.IQ push-button 5gang with thermostat Display, KNX - Berker B.IQ, glass black

Technical features

Architecture

Technical version	5gang
-------------------	-------

Functions

With room temperature controller	yes
----------------------------------	-----

Operating mode	controller operating modes: comfort, standby, night and frost/heat protection mode
----------------	------------------------------------------------------------------------------------

- for switch, push-button, dimmer, blind and thermostat functions
- with valve protection function
- button help function can be activated
- with room temperature timer and 2-week timer functions

Compatibility

- extension unit for light scene push-button

Controls and indicators

With LED indication	yes
---------------------	-----

Dimming	area dimming
---------	--------------

Number of buttons	5
-------------------	---

- text display (ASCII-format)
- blind operating concepts short-long-short and long-short parameterisable
- one push-button operation for switching, pushing, shutters and dimming
- LC display with symbols and illumination, switchable via object
- display of operating mode, controller lockout, room/outside temperature, time (clock required)
- with 2 additional display buttons

Connectivity

- with button blocking function

Measurement

- value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

Screen

With display	yes
--------------	-----

Materials

Colour of design line	glass black
-----------------------	-------------

RAL colour	RAL 9005 - Jet black
------------	----------------------

Material	glass
----------	-------

Material family	Glass
-----------------	-------

Dimensions

Assembling height	16,7 mm
-------------------	---------

Height	178,8 mm
--------	----------

Width	88,5 mm
-------	---------

LED control

LED with blue operation LED and 10 white status LEDs
(labelling field illumination)

Connection

- For flush-mounted bus coupling unit for B.IQ with thermostat

Settings

- end customer display scope parameterisable
- presence button parameterisable to extend comfort
- single and two push-button operation parameterisable
- programmable from ETS2, V1.2a

Scope of delivery

Bus connection included no

Accessories included

Inscribable, with labelling field no

- for installation in single standard wall boxes
- for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x
- for glass frames in the same "style" for additional applications, see the Design line B.7

Equipment

Product type: product type: B.IQ

- for heating and/or cooling mode with/without auxiliary step
- for individual single room temperature control
- control parameter for heating / cooling unit pre-set
- for continuous (PI) or switched (2-point) control of max. 2 control circuits

Use

Differentiation characteristic 2 - Sales Display

Software

Update with flash-controller technology

Safety

Halogen free no

- with dismantling protection
- alarm telegram after disconnection from bus coupling unit 1 bit, 1 or 2 byte

Use conditions

Operating temperature -5...45 °C

Energy efficiency class IV (2%)

- provision of the internal temperature value via communication object
- temperature measurement via internal temperature sensor and/or external communication object (weighting ratio parameterisable)

Identification

Application, usage	KNX - operating systems
Product family	product family: push-button
Release issue	2.6
Main design line	KNX - Berker B.IQ
Secondary design line(s)	Berker B.IQ, KNX
