



Cover for 2gang for push-button module with clear lens, KNX - Berker K.1/K.5, stainless steel matt, lacquered

Technical features

Architecture

Fixing mode flush-mounting

Functions

- operating concept "independent push-button" function predefined
- operating concept for "roller shutter/blind" function predefined
- switching of scenes (1..8) possible
- brightness value of the status LED for day/nighttime operation preset, change-over for day/nighttime operation possible
- integrated temperature sensor with output of the measured values
- Colour of status LED uniformly adjustable for complete device
- push-button functions: including switching, dimming, roller shutter/blind, timer, priority, operating mode changeover
- Function for manual interruption of automatic functions already triggered
- operating surfaces as buttons (single-surface operation) and rockers (two-surface operation)
- the brightness of status LEDs are individually adjustable for button/ rocker function
- brightness value of the status LEDs for day/nighttime operation adjustable via object or manually
- value transmitter for dimming, position, brightness temperature values 1 and 2 byte
- integrated temperature sensor with output of the measured values via object
- parameter defineable lock function
- button/rocker functions for switching, dimming, roller shutter/blind, value transmitter 1/2 byte, room thermostat extension unit, priority, scene, automatic control deactivation

Controls and indicators

- operating areas configurable as one or two-area operation
- with programming button and red programming LED

Voltage

Operating voltage over bus 21...32 V DC

Power

Power consumption, KNX ≈ 108 mW

Camera

- with 2 clear lenses for the RGB status display of the push-button module

Materials

| | |
|---------------------------|-----------------------------|
| Colour of design line | stainless steel |
| RAL colour | RAL 9022 - Pearl light grey |
| Material | thermoplastic |
| Surface appearance | matt |
| Type of surface treatment | Painted |

Dimensions

Height 55 mm

Connection

- with integral bus coupling unit
- bus connection via connecting terminal

80960373



IP20

Settings

| | |
|-------------------------------|--------------|
| Supported configuration modes | system, easy |
|-------------------------------|--------------|

Equipment

- with integrated buzzer for acoustic identification of the device within the system

Use

| | |
|--|-----------------|
| Differentiation characteristic 2 - Sales | with clear lens |
|--|-----------------|

Safety

| | |
|---------------------|------|
| Protection index IP | IP20 |
|---------------------|------|

- with dismantling protection

Use conditions

| | |
|-----------------------|------------|
| Operating temperature | -5...45 °C |
|-----------------------|------------|

| | |
|-------------------------------|--|
| Storage/transport temperature | -20...70 °C (storage at > 45°C reduces the service life) |
|-------------------------------|--|

- integrated temperature sensor with output of the measured values via object

Identification

| | |
|--------------------|-------------------------|
| Application, usage | KNX - operating systems |
|--------------------|-------------------------|

| | |
|----------------|-----------------------------|
| Product family | product family: push-button |
|----------------|-----------------------------|

| | |
|------------------|----------------------|
| Main design line | KNX - Berker K.1/K.5 |
|------------------|----------------------|

| | |
|--------------------------|-----------------------------|
| Secondary design line(s) | KNX, Berker K.1, Berker K.5 |
|--------------------------|-----------------------------|