




4432



IP44

**Combination key switch/SCHUKO socket outlet with hinged cover and imprint surface-mounted Screw terminals, Isopanzer IP44, dark grey/yellow**

Technical features

**Architecture**

Fixing mode	surface-mounting
Technical version	2pole can be switched on/off

**Configuration**

- with hollow base

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC
Rated current	16 A

**Electric current**

Switching current	10 A
-------------------	------

**Cover, door**

Cover	Complete housing
-------	------------------

**Materials**

Colour of design line	dark grey/yellow
Design lines special colours	dark grey/yellow
Colour	iron grey
Colour	dark grey
RAL colour	RAL 7011 - Iron grey
Material	thermoplastic
Surface appearance	glossy

**Dimensions**

Contact spacing	> 3 mm
-----------------	--------

**Installation, mounting**

Installation mode	for vertical mounting, for screw fastening
-------------------	--

**Connection**

Connection terminals	according to VDE 0620-1:2021-02
- with screw terminals	

**Cable**

- phase and neutral conductor wired-through
- with cable entry at top and bottom

**Equipment**

- for master-key systems

**Use**

---

Differentiation characteristic 3 - Sales	Screw terminals
--	-----------------

---

**Safety**

---

Protection index IP	IP44
---------------------	------

---

- without enhanced contact protection

---

**Identification**

---

Application, usage	Surface-mounted wet-room installation
Main design line	Isopanzer IP44

---

**Instructions**

---

Information text	Instead of SCHUKO socket outlets, any other devices from the ISO-reinforced IP44 and IP66 ranges with degree of protection IP44 can be used.
	Housing screws, hinged cover spring and axle made of stainless steel.

---