



75168690



## B.IQ push-button 4gang for light scenes KNX - Berker B.IQ, glass polar white

### Technical features

#### Architecture

Fixing mode	flush-mounting
-------------	----------------

#### Functions

With room temperature controller	no
----------------------------------	----

- light scene push-buttons can be cascaded
- retrieval, adjustment and storage of 8 light scenes

#### Controls and indicators

With LED indication	yes
---------------------	-----

Number of buttons	4
-------------------	---

- second operating level for setting load groups via 3-button actuation

#### Measurement

- dimming / position value transmitter 1 byte

#### Screen

With display	no
--------------	----

#### Materials

Colour of design line	glass polar white
-----------------------	-------------------

Colour	polarwhite
--------	------------

RAL colour	RAL 9010 - Pure white
------------	-----------------------

Material	glass
----------	-------

Surface appearance	glossy
--------------------	--------

Type of surface treatment	Painted
---------------------------	---------

#### Dimensions

Height	118,1 mm
--------	----------

Width	88,5 mm
-------	---------

#### LED control

LED	with blue operation LED and 8 white status LEDs (labelling field illumination)
-----	---

#### Connection

Number of load groups (increase on cascading)	8
---	---

- for bus coupling unit flush-mounted

#### Scope of delivery

Bus connection included	no
-------------------------	----

#### Accessories included

Inscribable, with labelling field	no
<ul style="list-style-type: none"><li>- for installation in single standard wall boxes</li><li>- for glass frames in the same "style" for additional applications, see the Design line B.7</li><li>- for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x</li></ul>	

#### Equipment

Number of actuation points	8
With anti-theft/dismantling protection	yes
Light scenes	max. 8
Product type:	product type: B.IQ

#### Safety

Protection index IP	IP20
Halogen free	no
<ul style="list-style-type: none"><li>- with dismantling protection</li></ul>	

#### Use conditions

Operating temperature	-5...45 °C
-----------------------	------------

#### Identification

Application, usage	KNX - operating systems
Product family	product family: push-button
Main design line	KNX - Berker B.IQ
Secondary design line(s)	KNX, Berker B.IQ