



80314116



**Switch actuator/blind actuator 4/2gang easy RMD for C load, 16 A with plug-in terminals, KNX, light grey**

Technical features

**Architecture**

Bus system	yes
Fixing mode	REG

**Functions**

Operating mode	any combined operation from drive and switching functions possible
----------------	--

- suitable to switch different external conductors
- with positioning function for blind and lamella position
- with safety functions e.g. for wind, rain, alarm
- with sun shade function
- For switching, e.g. of 4 independent loads or activation of 2 drives

**Controls and indicators**

Indicator lamp	yes
----------------	-----

- Manual operation can be activated via selection switch, thereby deactivation of the KNX function
- status LED integrated in the manual operation button
- manual operation buttons for on/off (up/down) and bus function on/off per channel/device
- with illuminated programming button

**Connectivity**

Bus system radio frequent	no
Bus system LON	no
Bus system Powernet	no

**Main electrical features**

Rated operational voltage Ue	230 V
Frequency	50/60 Hz
Rated current	16 A

**Voltage**

Operating voltage over bus	21...32 V DC
System supply voltage	30V DC via bus

**Electric current**

Bus current consumption (data transfer)	5 mA
Bus current consumption (idle)	3 mA
Maximum through current	16 A
Rated current	16 A

**Power**

Max. power with electronic transfo.	1200 W
Output power	2300 W
Max. switching power	3000 W
Conventional transformers	1600 VA
Electronic transformers	1200 W
C-load	yes

### Materials

Colour	light grey
--------	------------

### Dimensions

Width of rail mounted device (RMD)	4 modules
Height	90 mm

### Lighting control

Fluorescent lamps with electrical ballast (EB)	20 x 36 W
- uncompensated	1200 W

### Fluorescent bulbs control

Energy-saving lamps	20 x 23 W
Power lighting fluo lamps	18x23W
Fluorescent lamps parallel compensated	1500 W /200 µF

### LED control

Max number of LED/CFL lamps	18
230V LED lamps	18 x 23 W
Power LED	216 W
LED	Status LED integrated in manual operation button

### Incandescent bulbs control

Max. power with incandescent lamps	2300 W
230 V incandescent lamps and halogen lamps	2300 W

### Connection

Connection cross-sect. flexible conductor	0,75 / 2,5mm <sup>2</sup>
Connection cross-sect. rigid cable	0,75 / 2.5mm <sup>2</sup>
Type of load	C-Load
Conductor cross-section (flexible)	0,75...2,5 mm <sup>2</sup>
Conductor cross-section (rigid)	0,75...2,5 mm <sup>2</sup>
Type of contacts	4NO
Type of connection	quick connect
<ul style="list-style-type: none"> <li>- with integral bus coupling unit</li> <li>- with QuickConnect plug-in terminals</li> <li>- bus connection via connecting terminal</li> </ul>	

### Settings

Supported configuration modes	easy, system
- Switching time on change of direction is preset	

### Scope of delivery

Bus connection included	yes
-------------------------	-----

### Equipment

Number of outputs	4
Modular expandability	no
Different phases connectable	yes
With slide for manual switch	yes

### Use

Differentiation characteristic 3 - Sales	with plug-in terminals
--	------------------------

### Safety

Protection index IP	IP20
---------------------	------

### Use conditions

Operating temperature	-5...45 °C
Storage/transport temperature	-20...70 °C

### Identification

Device family	TXA
Main design line	KNX