



6765740001



Socket outlet with earthing pin with enhanced touch protection, with screw-in lift terminals, Berker Arsys, light bronze matt, aluminium lacquered

Technical features

Architecture

Fixing mode	flush-mounting
- 2pole + earth	

Connectivity

Type of USB port	other
------------------	-------

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Cover, door

Cover	Central cover plate
-------	---------------------

Materials

Colour of design line	light bronze
Colour	bronze
Colour	hellbronze optics
RAL colour	RAL 3012 - Beige red
Material / workmanship	aluminium lacquered
Material	Aluminium
Surface appearance	matt

Dimensions

Insertion depth	32 mm
Installation depth, flush-mounted boxes	32 mm
Mirror depth	14,7 mm

Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

Connection

Connection terminals	according to IEC 60884-1
- with screw-in lift terminals	

Use

Differentiation characteristic 2 - Sales	with enhanced touch protection
Differentiation characteristic 3 - Sales	with screw-in lift terminals

Safety

IK protection code against mechanical impacts	07
Enhanced contact protection	according to IEC 60884-1
- Enhanced contact protection	

Identification

Main design line	Berker Arsys
------------------	--------------