




283411



Universal rotary dimmer with centre plate (R, L, C) Soft-lock, Serie 1930/Glas, black glossy

Technical features

Functions

- bulb-preserving soft startup

Main electrical features

Nominal voltage 230 V

Voltage

Operating voltage 230 V AC

- voltage test possible without dismantling

Fuse

Fuse short-circuit and overload proof (electronic fuse)

Power

Dimmable conventional transformers 50...420 VA

connected load 50...420 W/VA

Loss power at full load ≈ 5 W

Electronic transformers 50...420 W

Measurement

Extension unit input with input for extension units insert for universal rotary dimmer

Materials

Colour of design line black

Colour black

Material Plastic/metal

Dimensions

Axis dimension Ø 4 mm

Incandescent bulbs control

230 V incandescent lamps and halogen lamps 50...420 W

Installation, mounting

Installation mode for screw fastening

Connection

Type of load universal

- with plug-in terminals

Scope of delivery

- with incremental encoder

Equipment

- phase cut-on or cut-off according to load type, self-learning
 - very low noise
 - with brightness memory
-

Use

Differentiation characteristic 3 - Sales Soft-lock

Use conditions

Operating temperature 5...25 °C

Identification

Release issue 2

Main design line Serie 1930/Glas

Secondary design line(s) Serie 1930, Serie 1930 Porzellan Made by
Rosenthal, Serie Glass, Series R.classic

Instructions

Information text Trouble-free operation will be obtained only with
Berker TronicÂ® transformers.
