



47431909



SCHUKO socket outlet Berker S.1/B.3/B.7, polar white matt

Technical features

AICHILECTULE	Arc	hite	cture
--------------	-----	------	-------

Design	according to DIN 49440
Fixing mode	flush-mounting

Connectivity

Type of USB port	other
Type of GGD port	Other

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Electric current

Rated current	16 A

Cover, door

Cover	Central cover plate
-------	---------------------

Materials

polar white	Colour of design line
polarwhite	Colour
white	Colour
RAL 9010 - Pure white	RAL colour
thermoplastic	Material
mat	Surface appearance

Dimensions

Insertion depth	32 mm
Installation depth, flush-mounted boxes	31 mm

Installation, mounting

to an Handan are also	and the second and a second
Installation mode	with spreader claws

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02

- with plug-in terminals

Safety

IK protection code against mecanical impacts	05
Protection index IP	IP20

- without enhanced contact protection



Identification

Main design line	Berker S.1/B.3/B.7
Secondary design line(s)	Berker S.1, Berker B.3, Berker B.7