



47431909



## SCHUKO socket outlet Berker S.1/B.3/B.7, polar white matt

### Technical features

#### Architecture

|             |                        |
|-------------|------------------------|
| Design      | according to DIN 49440 |
| Fixing mode | flush-mounting         |

#### Connectivity

|                  |       |
|------------------|-------|
| Type of USB port | other |
|------------------|-------|

#### Main electrical features

|                 |          |
|-----------------|----------|
| Nominal voltage | 250 V    |
| Rated voltage   | 250 V AC |
| Frequency       | 50/60 Hz |
| Rated current   | 16 A     |

#### Electric current

|               |      |
|---------------|------|
| Rated current | 16 A |
|---------------|------|

#### Cover, door

|       |                     |
|-------|---------------------|
| Cover | Central cover plate |
|-------|---------------------|

#### Materials

|                       |                       |
|-----------------------|-----------------------|
| Colour of design line | polar white           |
| Colour                | polarwhite            |
| Colour                | white                 |
| RAL colour            | RAL 9010 - Pure white |
| Material              | thermoplastic         |
| Surface appearance    | matt                  |

#### Dimensions

|   |       |
|---|-------|
| Insertion depth                         | 32 mm |
| Installation depth, flush-mounted boxes | 31 mm |

#### Installation, mounting

|                   |                     |
|-------------------|---------------------|
| Installation mode | with spreader claws |
|-------------------|---------------------|

#### Connection

|                          |                                 |
|--------------------------|---------------------------------|
| Connection terminals     | according to IEC 60884-1        |
| Connection terminals     | according to VDE 0620-1:2021-02 |
| - with plug-in terminals |                                 |

#### Safety

|   |      |
|---|------|
| IK protection code against mechanical impacts | 05   |
| Protection index IP                           | IP20 |
| - without enhanced contact protection         |      |

**Identification**

---

|                          |                                    |
|--------------------------|------------------------------------|
| Main design line         | Berker S.1/B.3/B.7                 |
| Secondary design line(s) | Berker S.1, Berker B.3, Berker B.7 |

---