



75261243

KNX controller 2.2 m KNX - Berker Arsys, stainless steel matt, lacquered

Technical features

Functions

- parameter defineable lock function

Compatibility

- also suitable as extension unit

Controls and indicators

Number of switching segments 72

Measurement

Detection field, semi-oval shaped ≈ 12 x 12 m

Reach distance

Range, frontal ≈ 12 m

Range, frontal (at 1.1 m installation height) ≈ 6 m

Range, side each ≈ 6 m

Range, side (at 1.1 m installation height) each ≈ 3 m

Cover, door

Cover with cover to limit detection angle to 90°

Detection

Number of detection levels 2

Detection angle 180 °

Sensor type detector of movement

Materials

Colour of design line stainless steel

RAL colour RAL 9022 - Pearl light grey

Material / workmanship lacquered

Material thermoplastic

Surface appearance matt

Dimensions

Dimensions assembling height 23,5 mm

Nominal mounting height 2,2 m

Lighting control

Response brightness, configurable 1...1000 lx / daytime operation

Connection

- for bus coupling unit flush-mounted

Settings

Supported configuration modes	system
Response sensitivity, settable	20...100 %
Delay time	≈ 10 s
Additional delay time programmable	130 ms...152 h
- with potentiometer for fine adjustment of the response sensitivity	

Equipment

Product type:	product type: movement
---------------	------------------------

Safety

Halogen free	no
--------------	----

Use conditions

Operating temperature	-5...45 °C
-----------------------	------------

Identification

Application, usage	KNX - sensors
Product family	product family: physical sensors
Main design line	KNX - Berker Arsys
Secondary design line(s)	KNX, Motion detector

Instructions

Information text	Application as for order no. 7526 11 ..
------------------	---