



6765102089



Socket outlet with earthing pin and LED orientation light enhanced contact protection, Screw-in lift terminals, Serie R.classic, polar white glossy

Technical features

Architecture

Fixing mode	flush-mounting
- 2pole + earth	

Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

Power

Power consumption	0.25 W/0.35 VA
-------------------	----------------

Cover, door

Cover	Central cover plate
-------	---------------------

Detection

- integrated brightness sensor that switches the orientation light on at twilight and off when there is sufficient brightness

Materials

Colour of design line	polar white
Colour	polarwhite
Colour	black
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	glossy

Lighting control

Switch-off brightness	≈ 4 lx
Switch-on brightness	≈ 2 lx
Light intensity (white)	0,2 cd

LED control

LED	long service life of the LED, white LED light
-----	---

Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

Connection

Conductor cross-section (rigid)	max. 2,5 mm ²
Connection terminals	according to IEC 60884-1
- with screw-in lift terminals	

Cable

- through-wiring possible, therefore also ideal for retrofitting
-

Equipment

- additional benefit by combination of a socket outlet with an orientation light
-

Use

Differentiation characteristic 2 - Sales	enhanced contact protection
Differentiation characteristic 3 - Sales	Screw-in lift terminals

Safety

-
- | | |
|-----------------------------|--------------------------|
| Enhanced contact protection | according to IEC 60884-1 |
|-----------------------------|--------------------------|
- Enhanced contact protection
-

Identification

Main design line	Serie R.classic
------------------	-----------------

Instructions

Information text	Caution! Items with special flush-mounted insert. Centre plates with LED orientation lights are not compatible with the standard socket outlets.
------------------	---
