product sheet 6768750069





6768750069

| Architecture | |
|--|-------------------------------|
| Fixing mode | flush-mountin |
| - 2pole + earth | |
| Connectivity | |
| Type of USB port | othe |
| Main electrical features | |
| Nominal voltage | 250 |
| Rated voltage | 250 V A |
| Frequency | 50/60 H |
| Rated current | 167 |
| Cover, door | |
| Cover | Central cover plat |
| Materials | |
| Colour of design line | polar whit |
| Colour | polarwhit |
| Colour | white |
| RAL colour | RAL 9010 - Pure white |
| Material | duroplasti |
| Surface appearance | gloss |
| Dimensions | |
| Insertion depth | 31,8 mn |
| Installation depth, flush-mounted boxes | 32 mn |
| Mirror depth | 14,7 mn |
| Installation, mounting | |
| Installation mode | with spreader claws |
| Connection | |
| Connection terminals | according to IEC 60884- |
| - with plug-in terminals | |
| Use | |
| Differentiation characteristic 2 - Sales | with enhanced touch protectio |
| Safety | |
| IK protection code against mecanical impacts | 0: |
| | according to IEC 60884- |

Socket outlet with earthing pin with enhanced touch protection, Berker Arsys, polar white glossy



Identification

Main design line

Berker Arsys