



6765092022



**Socket outlet with earthing pin and control LED with enhanced touch protection, Screw-in lift terminals, Berker R.1/R.3/R.8, red glossy**

Technical features

### Architecture

Fixing mode	flush-mounting
- 2pole + earth	

### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

### Cover, door

Cover	Central cover plate
-------	---------------------

### Materials

Colour of labelling	217,217,217
Design lines special colours	red
Colour	red
Colour	red
RAL colour	RAL 3003 - Ruby red
Material	thermoplastic
Material for printing	ABS red
Surface appearance	glossy

### Dimensions

Insertion depth	32 mm
-----------------	-------

### Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

### Connection

Connection terminals	according to IEC 60884-1
- with screw-in lift terminals	

### Equipment

Type of configuration	Laserdruck
-----------------------	------------

### Use

Differentiation characteristic 2 - Sales	with enhanced touch protection
Differentiation characteristic 3 - Sales	Screw-in lift terminals

### Safety

IK protection code against mechanical impacts	05
Enhanced contact protection	according to IEC 60884-1
- Enhanced contact protection	

**Identification**

---

Main design line	Berker R.1/R.3/R.8
Secondary design line(s)	Berker R.1, Berker R.3, Berker R.8

---

**Instructions**

---

Information text	Insert colour-coded.
------------------	----------------------

---