



75642134



**KNX Glass sensor 2gang with thermostat Display, integrated bus coupling unit, KNX - Berker TS Sensor - configured, glass aluminium**

Technical features

**Architecture**

Fixing mode	flush-mounting
Technical version	configured

**Functions**

With room temperature controller	yes
Operating mode	controller operating modes: comfort, standby, night and frost/heat protection mode
<ul style="list-style-type: none"> <li>- with valve protection function</li> <li>- for switch, push-button, dimmer, blind and thermostat functions</li> </ul>	

**Controls and indicators**

With LED indication	yes
<ul style="list-style-type: none"> <li>- operation by gently touching the sensor surfaces on the white LED</li> <li>- LED display with symbol display</li> <li>- display of operating mode, controller lockout, room/outside temperature, time (clock required)</li> <li>- with 2 additional display sensor surfaces</li> </ul>	

**Connectivity**

- with button blocking function

**Voltage**

- operation with non-choked output of KNX voltage supply possible (pay attention to current consumption)
- separate auxiliary power supply needed

**Power**

Current consumption	23 mA
---------------------	-------

**Measurement**

- value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

**Screen**

With display	yes
--------------	-----

**Materials**

Colour of labelling	105,105,105
Colour of design line	glass aluminium
Colour	aluminium
RAL colour	RAL 9006 - White aluminium
Material	glass
Surface appearance	glossy
Type of surface treatment	Tampography
Material family	Glass

### Dimensions

Depth	37,7 mm
Depth	5,7 mm
Dimensions (W x H x D)	86 x 160 x 5,7 mm
Height	160 mm
Width	86 mm

### LED control

LED	with blue operation LED and 4 white status LEDs
-----	---

### Installation, mounting

Installation mode	for vertical mounting
-------------------	-----------------------

### Connection

- with integral bus coupling unit
- bus connection via connecting terminal

### Settings

- single and two push-button operation parameterisable
- end customer display scope parameterisable

### Scope of delivery

Bus connection included	yes
-------------------------	-----

### Accessories included

Inscribable, with labelling field	no
-----------------------------------	----

- with adapter ring for dismantling protection and shadow gap formation
- for glass frames in the same "style" for additional applications, see the Design line B.7
- for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x

### Equipment

Number of actuation points	6
With anti-theft/dismantling protection	yes
Type of configuration	Laserdruck

- for heating and/or cooling mode with/without auxiliary step
- for individual single room temperature control
- control parameter for heating / cooling unit pre-set
- for continuous (PI) or switched (2-point) control

### Use

Differentiation characteristic 2 - Sales	Display
Differentiation characteristic 3 - Sales	integrated bus coupling unit

### Safety

Protection index IP	IP20
Halogen free	no

---

**Use conditions**

---

Operating temperature	-5...45 °C
Energy efficiency class	IV (2%)

---

- additional connection for external temperature sensor
- temperature measurement via internal temperature sensor or external communication object

---

**Identification**

---

Application, usage	KNX - operating systems
Main design line	KNX - Berker TS Sensor - configured
Secondary design line(s)	Berker TS Sensor, KNX

---

**Instructions**

---

Information text	Only suitable for KNX.
------------------	------------------------

---