



47442079



**SCHUKO socket outlet with hinged cover for accessible construction with tactile symbol, enhanced contact protection, Berker R.1/R.3, polar white glossy**

#### Technical features

##### Architecture

Design	according to DIN 49440
Fixing mode	flush-mounting

##### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

##### Electric current

Rated current	16 A
---------------	------

##### Cover, door

Cover	Central cover plate
-	with self-closing hinged covers

##### Materials

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Surface appearance	glossy

##### Dimensions

Insertion depth	32 mm
-----------------	-------

##### Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

##### Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1:2021-02
-	with plug-in terminals

##### Use cases

Barrier-free building	based on DIN 18040
-----------------------	--------------------

##### Use

Differentiation characteristic 1 - Sales	with tactile symbol
Differentiation characteristic 2 - Sales	enhanced contact protection

### Safety

IK protection code against mechanical impacts	05
Protection index IP	IP20
Enhanced contact protection	according to IEC 60884-1
Enhanced contact protection	according to VDE 0620-1:2021-02
- Enhanced contact protection	

### Identification

Main design line	Berker R.1/R.3
Secondary design line(s)	Berker R.1, Berker R.3, Berker R.8